

HX 88/F SERIES

HX88 SERIES



- Dual use can be used submersed or externally mounted, except HX8808.
- Long service life with low power consumption.
- Integral thermal protection.
- Robust construction with aluminum and ceramic shaft which can handle small particles.

1
YEAR
WARRANTY



UL
CERTIFIED



AQUATICS

MODEL	FLOW (Max)	HEIGHT (Max)	CONNECTOR	POWER	DIMENSIONS
HX8808	650 l/hour	1.2m	19mm	8W	130 x 60 x 85mm
HX8810/F	1050 l/hour	1.4m	19mm	12W	138 x 83 x 88mm
HX8815/F	1400 l/hour	1.8m	19mm	20W	138 x 83 x 88mm
HX8820/F	1950 l/hour	1.95m	19mm	25W	157 x 85 x 104mm
HX8825/F	2400 l/hour	2.1m	19mm	35W	157 x 85 x 104mm
HX8830/F	2900 l/hour	2.3m	25mm	45W	157 x 85 x 104mm
HX8840/F	4900 l/hour	3.0m	25mm	95W	239 x 102 x 149mm
HX8850/F	4000 l/hour	3.3m	25mm	70W	216 x 100 x 140mm
HX8860/F	5800 l/hour	4.1m	25mm	130W	242 x 145 x 170mm
HX8890/F	8000 l/hour	5.0m	25mm	200W	242 x 145 x 170mm

